

## POWER BARS: VERTICAL AND HORIZONTAL

### Horizontal model



### Features:

- UL approved
- Standard cord length is 15' (4.57M)
- Both Vertical and Horizontal models
- 15A and 20A available
- 19" EIA mount for horizontal models
- Standard colour is black



### Horizontal model

PART / MODEL NUMBER	RATED	MOUNT POSITION / SIZE	# OF OUTLETS / TYPE	PLUG	TYPE	SWITCHED
RFM-19-PBH-8	15A	HORIZONTAL / 19"W	8 OUTLETS (2-FR, 6-REAR) / 5-15R	STRAIGHT BLADE	5-15P	NO
RFM-19-PBHT	15A	HORIZONTAL / 19"W	6 OUTLETS / 5-15R	TWIST-LOCK	5-15P	YES
RFM-19-PBH-20A	20A	HORIZONTAL / 19"W	6 OUTLETS / 5-20R	STRAIGHT BLADE	5-20P	NO
RFM-19-PBHT-20A	20A	HORIZONTAL / 19"W	6 OUTLETS / 5-20R	TWIST-LOCK	L5-20P	NO

### Vertical model

PART / MODEL NUMBER	RATED	MOUNT POSITION / SIZE	# OF OUTLETS / TYPE	PLUG	TYPE	SWITCHED	WIDTH	LENGTH	DEPTH
RFM-48-PBV-18	15A	VERTICAL / 48"H	18 OUTLETS / 5-15R	STRAIGHT BLADE	5-15P	NO	1.6	48	1.5
RFM-52-PBVT	15A	VERTICAL / 52"H	8 OUTLETS / 5-15R	TWIST-LOCK	L5-15P	NO	1.6	48	1.149
RFM-62-PBV-24	15A	VERTICAL / 62"H	24 OUTLETS / 5-15R	STRAIGHT BLADE	5-15P	NO	1.6	62	1.5
RFM-76-PBVT	15A	VERTICAL / 76"H	12 OUTLETS / 5-15R	TWIST-LOCK	L5-15P	NO	1.6	77.5	1.149
RFM-52-PBV-20A	20A	VERTICAL / 52"H	8 OUTLETS / 5-20R	STRAIGHT BLADE	5-20P	NO	1.6	48	1.149
RFM-62-PBV-20A-24	20A	VERTICAL / 62"H	24 OUTLETS / 5-20R	STRAIGHT BLADE	5-20P	NO	1.6	62	1.5
RFM-62-PBVT-20A-24	20A	VERTICAL / 62"H	24 OUTLETS / 5-20R	TWIST-LOCK	L5-20P	NO	1.6	62	1.5

Other models available upon request - Consult factory for additional options